



CW MILL EQUIPMENT CO., INC.
P.O. Box 246 • Sabetha, Kansas 66534
(785) 284-3454 • FAX (785) 284-3601

IMK 62 -I8 Belts
1994-02 International
4700,4900 Series
7.3L(444E) W-WO/AC
W/O Air Brakes

INSTALLATION NOTES

1. Disconnect negative battery cable. Remove O.E.M. belt from the engine.
2. Install the pump mounting bracket on the front of the drivers side cylinder head with bolts provided. Tighten bolts securely. Install clutch pump and align it with the drive pulley. Tighten.
3. Install the new belt and route it according to the illustration.

CAUTION: Check all engine compartment hoses that may have been disturbed or re-routed during kit installation to be sure hoses are not kinked, that they do not touch any high temperature item, and that they do not touch any moving components.

NOTE: This kit is designed to operate successfully with the standard fan supplied by the manufacturer of your truck. Due to O.E.M. assembly tolerances and change, visually make certain that there is adequate clearance between fan and drive pulley and fan to radiator. It may be necessary to use a different fan spacer for clearance.

IMK 62 -I8 Belts

1994-02 International

4700,4900 Series

7.3L(444E) W-WO/AC

W/O AIR BRAKES

(DRAWING IS NOT AVAILABLE AT THIS TIME)